

# Home Office Fingerprint Keypad Lever Locks LA9-3

## Home Office Fingerprint Keypad Lever Locks LA9-3

Enjoy safety and security with the fingerprint and keypad door lock. This fingerprint lock is the perfect combination of top biometric technology with keypad technology. This keyless biometric fingerprint door lock has a tubular latch providing easy installation with no need to modify most existing doors. Fingerprint enrollment is quick and easy. Up to 138 users can be enrolled directly on the lock. Your finger is the only key you ever need for this lock. It is designed for unsurpassed security and convenience. It offers automatic locking, never leave your door unlocked again. It includes solid construction with the PCB sealed to prevent moisture, corrosion and loosening. This lockset is one of the most advanced security systems you'll ever install in your home or business

- Features:
- Wake up code is required to activate fingerprint
  - Adopts Optical Sensor with High Resolution (500 DPI)
  - 3 Ways to Unlock: Fingerprint + PIN, PIN, and Mechanical Key
  - Single Latch Easy to Install
  - Capacity: 138 Fingerprint templates maximum
  - Fingerprint can be enrolled and deleted on the lock directly. No software needed.
  - Wake up the lock with PIN
  - Unlock with PIN
  - Enable to enroll Fingerprint
  - Modify PIN
  - Delete enrolled fingerprints
  - Initialize the lock
  - Unique normal open state for meeting or gathering
- Installation:
- Door material: Metal Or Wooden Door
  - Fit door thickness from 1-3/8" - 2.0".
  - Adjustable latch: 2 3/8 or 2 3/4 inch backset.
  - Fit a standard 2-1/8" diameter hole.
- Specifications
- Fingerprint sensor: Optical sensor
  - Sensor resolution: 500 dpi
  - Authentication speed: <1 second
  - Authentication methods 1:N or 1:1
  - FRR: =0.0001%
  - Angle for putting finger:  $\pm 45^\circ$
  - Fingerprint scanning: Once to get one fingerprint template
  - Fingerprint template: All enrolled fingerprint template will be saved while replacing the batteries
  - User capacity: 138 max
  - Light jam: Sunlight resistant
  - Sensor surface: Optical glass with PVD coating
  - Operating voltage: 4 AA alkaline batteries, DC 4.5~6.0v
  - Battery life: Approx 12 months
  - Temperature for storage: -25°C-85°C
  - Static current: <10uA
  - Dynamic current: 110mA~180mA
- Contents
- keys (2pcs)
  - Strike (1pc)
  - Cylinder Cover opener (1pc)