

Deadbolt Lock DL240

Shepherd 240 Biometric Fingerprint Door Lock

Standalone Commercial Duty Fingerprint Biometric Locks--Fingerprint (Biometric) door locks are always an interesting product to use. Here are some more door locks that use fingerprint biometrics for access to rooms in your smart home...

Shepherd 240 biometric fingerprint door lock is designed to fit standard doors. It can be installed either by replacing existing single cylinder deadbolt, or in new doors, installed in place of single cylinder deadbolt. 4 screws affixes lock to the door. The Shepherd 240 biometric fingerprint door lock is capable of enrolling up to 4 administrators and 26 users with one fingerprint each. However, the manufacture of biometric fingerprint door lock recommends 1 or 2 administrators and 13 users with 2 fingerprints each. One finger from right hand and one finger from left hand.

This biometric fingerprint door lock also beeps 6 times with blinking red light when batteries are low. You would need to replace batteries in the fingerprint door lock. Another feature is that all of the saved fingerprints, or settings, will be kept during replacement of batteries. This biometric fingerprint door locks will be good for use in Apartments, Offices, Stores, Homes and Warehouse. Shepherd 240 biometric fingerprint door lock can be installed on either right or left hand doors. The deadbolt lock also comes with 3 overriding keys for emergency purposes if biometric fingerprint door lock is not working.

Security:

- 30 Fingerprint Capacity (4 Master Codes/26 User Codes)
- 30 Code (password) Capacity
- Optical CMOS Sensor
- Deadbolt made from hardened steel
- False Reject Rate, FRR : <2/100
- False Acceptance Rate, FAR : <1/10,000
- Scanning Time: <1 second
- Recognition Time: <2 seconds
- Translation Tolerance: <+/- 1.2" (>< +/-3mm)
- Rotation Tolerance: +/- 15°
- Power Supply: 4 AA alkaline batteries
- Battery Life: 5000 cycles with 1 set of 4 new long life batteries
- Operating Temperature: 0° F to 131° F (-18° C € ” 55° C)
- Humidity: 10% to 100%
- Approvals: CE, UL listed
- Low battery power warning.
- Emergency Key Override: 3 keys included.

Installation:

- Handing Type: Non-handed
- Easy to install. Only 3 additional 3/8" dia. through hole will need to be drilled.
- Will retrofit in a standard hole of 2-1/8" diameter.
- Installation Guide
- User Manual
- Installation Manual

Manufacture Warranty:

- 1 year warranty

Keyless Door Lock Size :

- Body Size: Inside and Outside Dimension: 5.9" x 3.3"x 1.4" (150mm x 83mm x 36mm)
- Latch Size: Adjustable deadbolt latch included: 2-3/8 " and 2-3/4 " backset
- Scanning Window: 0.47" x 0.63" (12mm x 16mm)
- Door Thickness: Will fit on any door from 1 1/2 inch to 2 inches thickness).

Additional Information:

- Usage: Designed for Home Office, Small Office, Warehouse
- Battery: Use 4 AA-size alkaline batteries or 4 AA-size rechargeable batteries (1.2V 1800mA.h)

Content Inside Packaging

- Outside lock assembly
- Inside lock assembly

- Inside rubber seal
- Outside rubber seal
- Deadbolt
- Strike lining box
- 3 emergency keys
- Deadbolt strike
- Wood screws
- Machine screws
- Attaching screws
- Installation manual
- Operation manual
- Cutout template